

Circuit Ready

Technology connectivity certification

The product

Logitech C925e

developed by **Logitech** has been certified
for Interoperability with **Circuit Meeting Room**
based on functional testing performed by Unify

Circuit Meeting Room OS V1R5.2.0 / **Logitech C925e** FW 7.54.1033

Supported features: Video camera

The test was conducted conforming to DIN EN ISO 9001. This certificate is only valid in conjunction with the full test report and the notes contained therein. The tests covered functional test and subjective acoustic test. **Please consider that the test report only covers the functionality of the interface.**

Munich, 07 May 2019



Functional Test Report

Circuit Meeting Room

with

Logitech C925e

Author: Christian Kaehler

Version: 1.0

Status: Released

Date: 07.05.2019

Table of Contents

1. Overview	3
1.1. Executive Summary	3
1.1.1. Basic Equipment	3
1.2. Test Strategy	3
1.3. Test Result Summary	3
1.3.1. Problems	3
1.3.2. Restrictions	3
1.3.3. Remarks	3
1.3.4. Setup	4
2. Test Results in Detail	5
2.1. Test cases	5
2.2. Remarks / Appendixes	5
3. Confirmation	6

History of Change

Version	Date	Description	Name
1.0	07.05.2019	Released	Christian Kaehler
0.1	29.03.2019	Draft	Christian Kaehler

1. Overview

1.1. Executive Summary

The functional tests were carried out at GVS (Global Vendor Support) test lab. The test cases are listed below. The test reports are automatically generated report.

1.1.1. Basic Equipment

Test environment	
Circuit	
Circuit Meeting Room OS	V1R5.2.0
Circuit Meeting Room Application	1.2.4800
Product FW	7.54.1033

1.2. Test Strategy

The certification test performed for Product is focused on audio basic functionality for

- video
- audio
- audio / video

The focus is on basic functionality and does not cover any quality measurements for audio or video streams. If additional features in the product are relevant for proper operation with Circuit Meeting Room then these are listed in the test cases.

1.3. Test Result Summary

For details please have a look at the test results

1.3.1. Problems

- No problems

1.3.2. Restrictions

- No restrictions

1.3.3. Remarks

- No remarks

1.3.4. Setup




Figure 1: Logical Topology Diagram Circuit Meeting Room

Circuit Meeting Room is tested in standard configuration: Network connected via Gigabit Ethernet, output display on Full-HD capable display (single screen configuration), for speakerphones a standard web cam is connected (and vice versa) to complete the configuration. Circuit public cloud service is used for operation.

Test Results in Detail

1.4. Test cases

Key	Test Description	Result	Comment
DTHSFT-4015	Connection via USB	Passed	Detected as "Logitech Webcam C925e" Connected via USB2.0
DTHSFT-4017	Conference: Audio output	Invalid	
DTHSFT-4018	Conference: Audio input	Invalid	Circuit Meeting Room does not use the built-in microphone
DTHSFT-4019	Conference: Video input	Passed	Reports 1920x1080p with 30p
DTHSFT-4020	Conference: Video output	Invalid	
DTHSFT-4021	Conference: Audio mute (local)	Invalid	
DTHSFT-4022	Conference: Mute sync with Circuit	Invalid	
DTHSFT-4023	Conference: Release from conference (sync with Circuit)	Invalid	
DTHSFT-4024	Connection and features via BT	Invalid	
DTHSFT-4025	Power saving	Passed	
DTHSFT-4026	Conference: Mute Circuit video	Passed	

1.5. Remarks / Appendixes

Explanation of acronyms:

CMR	Circuit Meeting Room
DUT	Device Under Test
INVALID	Test NOT applicable as not supported by DUT
FAILED	Test case NOT successful
PASSED	Test case successful

2. Confirmation

Testing personnel confirms that the test cases in chapter 0 were performed and that the results were as described in this document.

Date	Date
Name, Company	Name, Company