

Circuit Ready

Technology connectivity certification

The product

Speak 410

developed by **Jabra** has been certified
for Interoperability with **Circuit Meeting Room**
based on functional testing performed by Unify

Circuit Meeting Room OS V1R7.0.4 / Jabra Speak 410 FW 1.12.0

Supported features: Speakerphone with Circuit integration

The test was conducted conforming to DIN EN ISO 9001. This certificate is only valid in conjunction with the full test report and the notes contained therein. The tests covered functional test and subjective acoustic test. **Please consider that the test report only covers the functionality of the interface.**

Munich, 27 April 2020



Functional Test Report

Circuit Meeting Room

With

Jabra Speak 410

Author:	Christian Kaehler
Version:	1.0
Status:	Released
Date:	27.04.2020

Table of Contents

1. Overview	3
1.1. Executive Summary	3
1.1.1. Basic Equipment	3
1.2. Test Strategy	3
1.3. Test Result Summary	3
1.3.1. Problems	3
1.3.2. Restrictions	3
1.3.3. Remarks	3
1.3.4. Setup	4
1.4. Test cases	5
1.5. Remarks / Appendixes	5

History of Change

Version	Date	Description	Name
1.0	27.04.2020	Released – retest with V1R7.0.4	Christian Kaehler

1. Overview

1.1. Executive Summary

The functional tests were carried out at GVS (Global Vendor Support) test lab. The test cases are listed below. The test reports are automatically generated report.

1.1.1. Basic Equipment

Test environment	
Circuit Meeting Room OS	V1R7.0.4
Circuit Meeting Room Application	1.2.7602
Jabra Speak 410 FW	1.12.0

1.2. Test Strategy

The certification test performed for Jabra Speak 410 is focused on audio basic functionality for

video

audio

audio / video

The focus is on basic functionality and does not cover any quality measurements for audio or video streams. If additional features in the product are relevant for proper operation with Circuit Meeting Room then these are listed in the test cases.

1.3. Test Result Summary

For details please have a look at the test results

1.3.1. Problems

- No problems

1.3.2. Restrictions

- No restrictions

1.3.3. Remarks

- No remarks

1.3.4. Setup




Figure 1: Logical Topology Diagram Circuit Meeting Room

Circuit Meeting Room is tested in standard configuration: Network connected via Gigabit Ethernet, output display on Full-HD capable display (single screen configuration), for speakerphones a standard web cam is connected (and vice versa) to complete the configuration. Circuit cloud service is used for operation.

Test Results in Detail

1.4. Test cases

Key	Test Description	Result	Comment
DTHSFT-5382	Connection via USB	Passed	DUT connected via USB2.0 (but also working with USB3.1)
DTHSFT-5383	Conference: Audio output	Passed	
DTHSFT-5384	Conference: Audio input	Passed	
DTHSFT-5385	Conference: Video input	Invalid	
DTHSFT-5386	Conference: Audio mute (local)	Invalid	Circuit does support integration with DUT
DTHSFT-5387	Conference: Mute sync with Circuit	Passed	
DTHSFT-5388	Conference: Release from conference (sync with Circuit)	Passed	
DTHSFT-5389	Connection and features via BT	Invalid	Not supported by DUT. For BT - see Jabra Speak 510
DTHSFT-5390	Power saving	Passed	
DTHSFT-5391	Telephony - interaction	Invalid	
DTHSFT-5392	Conference: Long duration call	Passed	
DTHSFT-5393	Conference: Manual testing - mixed scenarios	Passed	

1.5. Remarks / Appendixes

Explanation of acronyms:

CMR	Circuit Meeting Room
DUT	Device Under Test
INVALID	Test NOT applicable as not supported by DUT
FAILED	Test case NOT successful
PASSED	Test case successful