Circuit Ready

Technology connectivity certification

The product

Jabra PanaCast

developed by Jabra has been certified
for Interoperability with Circuit Meeting Room
based on functional testing performed by Unify

Circuit Meeting Room OS V1R6.0.0 / Product FW 0.3.7.18

Supported features: Video camera

The test was conducted conforming to DIN EN ISO 9001. This certificate is only valid in conjunction with the full test report and the notes contained therein. The tests covered functional test and subjective acoustic test. **Please consider that the test report only covers the functionality of the interface.**

Munich, 19 September 2019

UNIFY
atos collaboration solutions

Functional Test Report

Circuit Meeting Room

with

Jabra PanaCast

Author:	Christian Kaehler
Version:	1.0
Status:	Released
Date:	19.09.2019

Table of Contents

History of Change

Version	Date	Description	Name
1.0	19.09.2019	Released	Christian Kaehler
0.1	04.09.2019	Draft	Christian Kaehler

Christian Kaehler   Released

Test Report of Jabra PanaCast with Circuit Meeting Room

1. Overview

1.1. Executive Summary

The functional tests were carried out at GVS (Global Vendor Support) test lab.
The test cases are listed below. The test reports are automatically generated report.

1.1.1. Basic Equipment

Test environment	
Circuit	
Circuit Meeting Room OS	V1R6.0.0
Circuit Meeting Room Application	1.2.5601
Jabra PanaCast FW	0.3.7.18

1.2. Test Strategy

The certification test performed for Jabra PanaCast is focused on audio basic functionality for

☒video

☐audio

☐audio / video

The focus is on basic functionality and does not cover any quality measurements for audio or video streams. If additional features in the product are relevant for proper operation with Circuit Meeting Room then these are listed in the test cases.

1.3. Test Result Summary

For details please have a look at the test results

### 1.3.1. Problems

- No problems

1.3.2. Restrictions

- DUT does not support setting line frequency via Circuit Meeting Room configuration option (use the "Auto Detection" mode on Jabra PanaCast – this can be verified or configured with the Jabra Direct tool).

1.3.3. Remarks

- No remarks

Christian Kaehler

Test Report of Jabra PanaCast with Circuit Meeting Room

1.3.4. Setup

Figure 1: Logical Topology Diagram Circuit Meeting Room

Circuit Meeting Room is tested in standard configuration: Network connected via Gigabit Ethernet, output display on Full-HD capable display (single screen configuration), for speakerphones a standard web cam is connected (and vice versa) to complete the configuration. Circuit public cloud service is used for operation.

Christian Kaehler

Test Report of Jabra PanaCast with Circuit Meeting Room

Test Results in Detail

1.4. Test cases

Key	Test Description	Result	Comment
DTHSFT-4515	Connection via USB	Passed	Connected via USB3.0. Detected as "Jabra PanaCast"
DTHSFT-4516	Conference: Audio output	Invalid	
DTHSFT-4517	Conference: Audio input	Invalid	CMR does not use the camera mic
DTHSFT-4518	Conference: Video input	Passed	1920*1080p, 30 fps LED blue when in idle LED white when in call LED blue blinking / blue when video is stopped via Circuit
DTHSFT-4519	Conference: Video output	Invalid	
DTHSFT-4520	Conference: Audio mute (local)	Invalid	
DTHSFT-4521	Conference: Mute sync with Circuit	Invalid	
DTHSFT-4522	Conference: Release from conference (sync with Circuit)	Invalid	
DTHSFT-4523	Connection and features via BT	Invalid	
DTHSFT-4524	Power saving	Passed	
DTHSFT-4525	Telephony - interaction	Invalid	
DTHSFT-4526	Conference: Long duration call	Passed	
DTHSFT-4527	Conference: Manual testing - mixed scenarios	In Progress	

Christian Kaehler

1.5. Remarks / Appendixes

Explanation of acronyms:

CMR	Circuit Meeting Room
DUT	Device Under Test
INVALID	Test NOT applicable as not supported by DUT
FAILED	Test case NOT successful
PASSED	Test case successful